

# CASTER GUIDELINES

## About Cres Cor

### COMPANY HISTORY

When your business is on a roll we hope it's in Cres Cor's hot cabinets, ovens, utility cabinets, racks, dollies and a host of other Cres Cor quality products.

Cres Cor, a family owned company, has been a moving force in the foodservice industry since 1936 and is centrally headquartered near Cleveland, Ohio. With over 275,000 square feet of state-of-the-art manufacturing and distribution facilities, we have made a commitment to unsurpassed reliability and superb customer service.

### COMPANY FOCUS

"Our focus is to continually bring new ideas and exciting, labor and money saving products to market" says Cliff Baggott, Cres Cor's president. "We are a 76 year 'young' company always striving to improve our products, processes, and ourselves."

### COMPANY TODAY

Today, you can visit Cres Cor many different ways. Come see our product information on our website, call our Customer Care staff directly at our world headquarters, or contact your local Cres Cor sales representative.

**Cres Cor**  
5925 Heisley Rd.  
Mentor, OH 44060-1833  
Phone: 877-CRESCOR (273-7267)  
Fax: 800-822-0393  
[www.crescor.com](http://www.crescor.com)



**CRESCOR®**

**CRESCOR®**



### Caster Application Guide

| Caster Type  | Carpet      | Tile        | Concrete/Asphalt/<br>Outdoor | Quiet       | Consistently Heavy<br>Loads > 500 lbs. |
|--|-------------|-------------|------------------------------|-------------|--|
| Standard Modulus<br>(5" dia. x 1 1/4" wide)              | Good        | Good        | Good                         | Good        | Good                                   |
| Standard Modulus Wide<br>(5" dia. x 2" wide)             | Good        | Better      | Better                       | Good        | Better                                 |
| Polyurethane<br>(6" dia. x 2" wide or 8" dia. x 2" wide) | <b>Best</b> | <b>Best</b> | Better                       | Good        | <b>Best</b>                            |
| Pneumatic, All Terrain<br>(8" dia. x 2" wide)            | Good        | Better      | <b>Best</b>                  | Good        | Not recommended                        |
| Hi-Modulus<br>(6" dia. x 2" wide or 8" dia. x 2" wide)   | Better      | Good        | Better                       | <b>Best</b> | Not recommended                        |

Larger and wider casters are upgrade options for overall better performance.



## CRES COR STANDARD CASTERS



0569-310

### 2-1/2" Swivel Polyolefin

- 1-1/8" wide
- Load capacity 150 lbs. ea.
- Temp range -20°/+180°F

Standard on under counter hot cabinets and ovens.



0569-313

### 3" Swivel Modulus Wheel

- 1-1/8" wide
- Load capacity 160 lbs. ea.
- Temp range -30°/+160°F

Standard on H339X series under counter hot cabinets.



0569-306

### 5" Swivel Modulus Wheel

- 1-1/4" wide
- Load capacity 250 lbs. ea.
- Temp range -40°/+180°F

Standard on all full size hot cabinets, ovens and single door refrigerated cabinet.



0569-290

### 6" Modulus Wheel

- 2" wide
- Load capacity 450 lbs. ea.
- Temp range -40°/+180°F

Standard on all double door refrigerated cabinets and CCB Banquet Cabinets.



0569-000

### 5" Swivel Modulus Wheel

- 2" wide
- Load capacity 250 lbs. ea.
- Temp range -45°/+180°F

Special Non-stocking Caster



0569-304

### 5" Polyurethane Wheel

- 1-1/4" wide
- Load capacity 300 lbs. ea.
- Temp range -30°/+180°F



0569-320

### 6" Polyurethane Wheel

- 2" wide
- Load capacity 800 lbs. ea.
- Temp range -30°/+180°F



1206-025

### 4" Leg

- Black plastic

Standard on Countertop hot cabinet.



1206-067

### 6" Leg

- Stainless Steel



0569-273

### 6" Polyurethane

- 1-1/4" wide
- Load capacity 300 lbs. ea.
- Temp range -30°/+180°F



0569-269

### 8" Polyurethane Wheel

- 2" wide
- Load capacity 1000 lbs. ea.
- Temp range -30°/+180°F
- Best for heaviest loads



0569-295

### 8" Hi-Modulus Wheel

- 2-1/4" wide heavy duty
- Load capacity 450 lbs. ea.
- Temp range -40°/+160°F
- Softer & quieter
- Great for fragile loads



0569-281

### 8" Pneumatic

- 2" wide heavy duty
- Load capacity 310 lbs. ea.
- Temp range -20°/+160°F
- Great for outdoors
- No-flat foam filled option also available

Standard on our latest innovative HotCube<sup>3</sup>